

PLAT OF RETRACEMENT AND PARTIAL SUBDIVISION OF SECTIONS 28 & 29, A PORTION OF THE LINCOLN NATIONAL FOREST PROPERTY LINE.

NW-SE 1/64 CORNER OF SECTION 29

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, with cap mkd:

USDA-FS
T19S R14E
S29
NW-SE 1/64
L.S. 6846
1982

from which bearing trees:
A pine, 12 ins. diam., bears S.06°34'E., 41.5 lks. dist., mkd. "XBT"
A pine, 12 ins. diam., bears S.81°09'W., 11.0 lks. dist., mkd. "XBT"
A stone mound bears N.43°12'E., 18.5 lks. dist., (unmarked)

C-N-S 1/64 CORNER OF SECTION 29

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 4 ins. in the ground, encircled by a mound of stone raised to aluminum cap marked:

USDA-FS
T19S R14E
S29
C-N-S 1/64
L.S. 6846
1982

from which bearing trees:
A pine, 6 ins. diam., bears S.18°03'W., 31.8 lks. dist., mkd. "XBT"
A pine, 8 ins. diam., bears N.48°43'W., 29.8 lks. dist., mkd. "XBT"
A stone mound bears N.02°14'E., 12.3 lks. dist., (unmarked)

C 1/4 CORNER OF SECTION 29

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 5 ins. in the ground, encircled by a mound of stones raised to aluminum cap marked:

USDA-FS
T19S R14E
S29
C 1/4
L.S. 6846
1982

from which bearing trees:
A pine, 14 ins. diam., bears S.66°21'E., 73.2 lks. dist., mkd. "XBT"
A juniper, 16 ins. diam., bears S.27°25'W., 54.2 lks. dist., mkd. "XBT"
A stone mound bears S.47°56'E., 9.1 lks. dist., mkd. "FS C-1/4"

C-E-W 1/64 CORNER OF SECTION 29

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 21 ins. in the ground, with cap mkd:

USDA-FS
T19S R14E
S29
C-E-W 1/64
L.S. 6846
1982

from which bearing trees:
A pine, 8 1/2 ins. diam., bears S.50°30'W., 64.7 lks. dist., mkd. "XBT"
A pinon, 9 1/2 ins. diam., bears N.28°W., 58.0 lks. dist., mkd. "XBT"
A stone mound bears S.14°W., 18.5 lks. dist., (unmarked)

SE-NW 1/64 CORNER OF SECTION 29

Set an aluminum post 2 1/2 ins. diam., 30 ins. long, 6 ins. in the ground, encircled with a mound of stones raised to aluminum cap marked:

USDA-FS
T19S R14E
S29
SE-NW 1/64
L.S. 6846
1982

from which bearing trees:
A pinon, 10 ins. diam., bears N.79°38'W., 32 lks. dist., mkd. "XBT"
A pinon, 10 ins. diam., bears S.38°30'W., 19.8 lks. dist., mkd. "XBT"
A stone mound bears S.69°13'W., 15.5 lks. dist., (unmarked)

C-S-N 1/64 CORNER OF SECTION 29

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 14 ins. in the ground, encircled with a mound of stones raised to aluminum cap marked:

USDA-FS
T19S R14E
S29
C-S-N 1/64
L.S. 6846
1982

from which bearing trees:
A pinon, 6 ins. diam., bears N.39°W., 25.2 lks. dist., mkd. "XBT"
A pine, 12 ins. diam., bears N.37°49'E., 68.6 lks. dist., mkd. "XBT"

C-S-NE 1/64 CORNER OF SECTION 29

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 28 ins. in the ground, with cap mkd:

USDA-FS
T19S R14E
S29
C-S-NE 1/64
L.S. 6846
1982

from which bearing trees:
A pine, 17 ins. diam., bears N.71°53'E., 147.6 lks. dist., mkd. "XBT"
A pine, 9 ins. diam., bears S.11°53'E., 86.4 lks. dist., mkd. "XBT"
A stone mound bears N.01°20'W., 33.8 lks. dist., (unmarked)

E 1/16 CORNER OF SECTIONS 20 & 29

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 16 ins. in the ground, encircled by a mound of stones raised to aluminum cap marked:

USDA-FS
T19S R14E
S20
E 1/16
L.S. 6846
1982

from which bearing trees:
A pinon, 6 ins. diam., bears N.14°38'W., 46.4 lks. dist., mkd. "XBT"
A pinon, 5 ins. diam., bears N.75°41'E., 51.4 lks. dist., mkd. "XBT"
A stone mound bears N.67°37'W., 13.6 lks. dist., (unmarked)

E-E 1/64 CORNER OF SECTIONS 20 & 29

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 22 ins. in the ground, with cap mkd:

USDA-FS
T19S R14E
S20
E-E 1/64
L.S. 6846
1982

from which bearing trees:
A pine, 10 ins. diam., bears N.19°14'E., 46.7 lks. dist., mkd. "XBT"
A pine, 10 ins. diam., bears S.61°06'E., 35.5 lks. dist., mkd. "XBT"
A stone mound bears S.89°23'W., 21.8 lks. dist., (unmarked)

NE-NE 1/64 CORNER OF SECTION 29

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, with cap mkd:

USDA-FS
T19S R14E
S29
NE-NE 1/64
L.S. 6846
1982

from which bearing trees:
A juniper, 19 ins. diam., bears N.43°36'E., 22.3 lks. dist., mkd. "XBT"
A pinon, 5 ins. diam., bears N.43°43'W., 19.7 lks. dist., mkd. "XBT"
A stone mound bears S.59°26'W., 10.6 lks. dist., (unmarked)

N-N 1/64 CORNER OF SECTIONS 28 & 29

Set an aluminum post 2 1/2 ins. diam., 30 ins. long, 22 ins. in the ground, encircled with a mound of stones raised to aluminum cap marked:

USDA-FS
T19S R14E
S29 | S28
N-N 1/64
L.S. 6846
1982

from which bearing trees:
A pine, 9 ins. diam., bears N.32°48'W., 51.4 lks. dist., mkd. "XBT"
A pine, 11 ins. diam., bears N.34°47'E., 17.9 lks. dist., mkd. "XBT"
A stone mound bears N.39°E., 9.7 lks. dist., (unmarked)

NE-NW 1/64 CORNER OF SECTION 28

Set an aluminum post 2 1/2 ins. diam., 30 ins. long, 8 ins. in the ground, encircled by a mound of stone raised to aluminum cap marked:

USDA-FS
T19S R14E
S28
NE-NW 1/64
L.S. 6846
1982

from which bearing trees:
A pinon, 11 ins. diam., bears N.29°W., 81.5 lks. dist., mkd. "XBT"
A pinon, 8 ins. diam., bears N.36°E., 60.6 lks. dist., mkd. "XBT"

SE-NW 1/64 CORNER OF SECTION 28

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 20 ins. in the ground, with cap mkd:

USDA-FS
T19S R14E
S28
SE-NW 1/64
L.S. 6846
1982

from which bearing trees:
A pine, 9 ins. diam., bears N.82°E., 33.3 lks. dist., mkd. "XBT"
A pine, 10 ins. diam., bears S.10°E., 54.5 lks. dist., mkd. "XBT"

S-N 1/64 CORNER OF SECTIONS 28 & 29

Set an aluminum post 2 1/2 ins. diam., 30 ins. long, on top of large imbedded boulder encircled with a large mound of stones raised to aluminum cap marked:

USDA-FS
T19S R14E
S29 | S28
S-N 1/64
L.S. 6846
1982

from which bearing trees:
A pine, 7 ins. diam., bears S.11°14'E., 28.0 lks. dist., mkd. "XBT"
A pine, 13 ins. diam., bears S.82°11'W., 45.8 lks. dist., mkd. "XBT"

SE-NE 1/64 CORNER OF SECTION 29

Set an aluminum post, 2 1/2 ins. diam., 30 ins. long, 25 ins. in the ground, with cap mkd:

USDA-FS
T19S R14E
S29
SE-NE 1/64
L.S. 6846
1982

from which bearing trees:
A pine, 9 ins. diam., bears S.73°24'E., 44.1 lks. dist., mkd. "XBT"
A pine, 9 ins. diam., bears S.08°54'E., 36.7 lks. dist., mkd. "XBT"
A stone mound bears N.59°E., 13.6 lks. dist., (unmarked)

C-E-E 1/64 CORNER OF SECTION 29

Set an aluminum post 2 1/2 ins. diam., 30 ins. long, 25 ins. in the ground, with cap mkd:

USDA-FS
T19S R14E
S29
C-E-E 1/64
L.S. 6846
1982

from which bearing trees:
A pine, 11 ins. diam., bears N.44°52'E., 37.9 lks. dist., mkd. "XBT"
A pine, 12 ins. diam., bears S.74°30'E., 32.9 lks. dist., mkd. "XBT"
A stone mound bears N.59°47'E., 16.1 lks. dist., (unmarked)

C-W-E 1/64 CORNER OF SECTION 29

Set an aluminum post 2 1/2 ins. diam., 30 ins. long, 20 ins. in the ground, with cap mkd:

USDA-FS
T19S R14E
S29
C-W-E 1/64
L.S. 6846
1982

from which bearing trees:
A pine, 16 ins. diam., bears S.09°E., 56.4 lks. dist., mkd. "XBT"
A pine, 9 ins. diam., bears S.82°W., 11.4 lks. dist., mkd. "XBT"
A stone mound bears N.72°E., 4.8 lks. dist., (unmarked)

C 1/4 CORNER OF SECTION 28

Set an aluminum post 2 1/2 ins. diam., 30 ins. long, 12 ins. in the ground, encircled with a mound of stones raised to aluminum cap marked:

USDA-FS
T19S R14E
S28
C 1/4
L.S. 6846
1982

from which bearing trees:
A pinon, 13 ins. diam., bears N.47°43'E., 6.4 lks. dist., mkd. "XBT"
A pinon, 6 ins. diam., bears N.56°26'W., 56.8 lks. dist., mkd. "XBT"
A stone mound with one stone marked "C 1/4 F.S.", bears S.79°23'W., 72.0 lks. dist.

STATE OF NEW MEXICO
OTERO COUNTY
FILED FOR RECORD IN MY OFFICE
This 4 day of May 1982
At 1:30 o'clock P.M. and duly recorded
in Book No. 25 Page 47-48
Ruth A. Sanchez
Margaret D. Sanchez

[Signature]

PREPARED BY: WILSON SURVEYING COMPANY, INC.
1021 B WYOMING AVENUE EL PASO, TEXAS (915) 533-3448
1716 AVENUE M LUBBOCK, TEXAS (806) 763-3388

U.S. Department of Agriculture
FOREST SERVICE
SOUTHWESTERN REGION, ALBUQUERQUE, N.MEX.
RECORD OF SURVEY

Checked by: _____ Approved by: _____ Date: _____

Bk 25 Pg 48

#73876