

# SURVEY AND MONUMENTATION SECTIONS 5,6,7 AND 8, T.18S., R.15E., N.M.P.M., OTERO COUNTY, NEW MEXICO



NOTE: 1) BASIS OF BEARINGS FOR THIS SURVEY AND PLAT IS S.00°24'30"E., BETWEEN THE NORTHEAST CORNER OF SECTION 12 AND THE EAST 1/4 CORNER OF SECTION 12, T.18S., R.14E., SAID BEARING WAS TAKEN FROM A SURVEY AND MONUMENTATION PLAT PREPARED BY SOUTHWEST ENGINEERING, SAID PLAT IS FILED IN BOOK 40, PAGES 57-59, OTERO COUNTY RECORDS.

I, WYATT A. SPARKS, A REGISTERED PROFESSIONAL SURVEYOR UNDER THE LAWS OF THE STATE OF NEW MEXICO, HEREBY CERTIFY THAT THIS PLAT WAS PREPARED FROM FIELD NOTES OF AN ACTUAL SURVEY MEETING THE MINIMUM REQUIREMENTS OF THE STANDARDS FOR LAND SURVEYS AND IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF, AND THAT NO ENCROACHMENTS EXIST EXCEPT AS NOTED HEREON AND THAT ALL IMPROVEMENTS ARE SHOWN IN THEIR CORRECT LOCATION RELATIVE TO RECORD BOUNDARIES AS LOCATED BY THIS SURVEY.

DATE: Sept. 1, 1994

WYATT A. SPARKS  
PROFESSIONAL SURVEYOR  
N.M. 8487

### LEGEND

- CORNER MONUMENTED OR REMONUMENTED ○
- FOUND U.S.G.L.O. BRASS CAP ⊙
- FOUND U.S.F.S. ALUMINUM CAP □
- FOUND ORIGINAL STONE MONUMENT ●
- NATIONAL FOREST BOUNDARY ———

ACREAGE PER SECTION  
SECTION 5 = 38.751 ACRES  
SECTION 6 = 117.075 ACRES  
SECTION 7 = 36.947 ACRES  
SECTION 8 = 157.973 ACRES

STATE OF NEW MEXICO }  
COUNTY OF OTERO } SS

RECORDED IN THE OFFICE OF THE COUNTY CLERK AND EX-OFFICIO RECORDED OF OTERO COUNTY, NEW MEXICO, AT 3:35 O'CLOCK, P.M., THIS 1st DAY OF September, 1994

Mary D. Quintana COUNTY CLERK  
BY Carla Silva  
RECEPTION NO. 9878 BOOK 40, PAGE 13-14

ALL CORNERS MONUMENTED AS A RESULT OF THIS SURVEY CONSIST OF AN ALUMINUM POST, 2 1/2 INCHES DIAMETER, 30 INCHES LONG WITH U.S.D.A. FOREST SERVICE CAP STAMPED AS SHOWN IN THE FOLLOWING NOTES.


CORNER OF SECTIONS 5,6,7 AND 8

ORIGINAL STONE NOT FOUND. SET AN ALUMINUM POST, 30 INCHES LONG, ON BEDROCK, BUILT A 2 FOOT COLLAR OF STONE AROUND ALUMINUM POST, WITH CAP MARKED,




1/4 CORNER OF SECTIONS 5 AND 8

A LIMESTONE 16x8x6 INCHES SET IN A SUPPORTING MOUND ON STONE MARKED 1/4 ON NORTH FACE. SET ALUMINUM POST, 30 INCHES LONG ALONG SIDE ORIGINAL STONE IN A SUPPORTING MOUND OF STONE WITH CAP MARKED,




1/4 CORNER OF SECTIONS 6 AND 7

ORIGINAL WITNESS CORNER NOT FOUND. SET ALUMINUM POST, 30 INCHES LONG, 26 INCHES IN GROUND WITH CAP MARKED,




W 1/16 CORNER OF SECTIONS 5 AND 8

SET AN ALUMINUM POST, 30 INCHES LONG, 26 INCHES IN GROUND WITH CAP MARKED,



S 1/16 CORNER OF SECTIONS 5 AND 6

SET AN ALUMINUM POST, 30 INCHES LONG, 24 INCHES IN GROUND WITH CAP MARKED,



SW 1/16 CORNER SECTION 5

SET AN ALUMINUM POST, 30 INCHES LONG, 24 INCHES IN GROUND WITH CAP MARKED,




W 1/16 CORNER OF SECTIONS 6 AND 7

SET AN ALUMINUM POST, 30 INCHES LONG, 24 INCHES IN GROUND WITH CAP MARKED,




C-S 1/16 CORNER OF SECTION 6

SET AN ALUMINUM POST, 30 INCHES LONG, ON BEDROCK, BUILT A 2 FOOT COLLAR OF STONE AROUND AN ALUMINUM POST WITH CAP MARKED;




SW 1/16 CORNER OF SECTION 6

SET AN ALUMINUM POST, 30 INCHES LONG, ON BEDROCK, BUILT A 2 FOOT COLLAR OF STONE AROUND AN ALUMINUM POST WITH CAP MARKED;




NW 1/16 CORNER OF SECTION 7

SET AN ALUMINUM POST, 30 INCHES LONG, ON BEDROCK, BUILT A 2 FOOT COLLAR OF STONE AROUND AN ALUMINUM POST WITH CAP MARKED;




N 1/16 CORNER OF SECTIONS 7 AND 8

SET AN ALUMINUM POST, 30 INCHES LONG, ON BEDROCK, BUILT A 2 FOOT COLLAR OF STONE AROUND AN ALUMINUM POST WITH CAP MARKED;




NW 1/16 CORNER OF SECTION 7

SET AN ALUMINUM POST, 30 INCHES LONG, ON BEDROCK, BUILT A 2 FOOT COLLAR OF STONE AROUND AN ALUMINUM POST WITH CAP MARKED;




C-W 1/16 CORNER OF SECTION 8

SET AN ALUMINUM POST, 30 INCHES LONG, ON BEDROCK, BUILT A 2 FOOT COLLAR OF STONE AROUND AN ALUMINUM POST WITH CAP MARKED;




C 1/4 CORNER OF SECTION 8

SET AN ALUMINUM POST, 30 INCHES LONG, ON BEDROCK, BUILT A 2 FOOT COLLAR OF STONE AROUND AN ALUMINUM POST WITH CAP MARKED;



C-E 1/16 CORNER OF SECTION 8

SET AN ALUMINUM POST, 30 INCHES LONG, ON BEDROCK, BUILT A 2 FOOT COLLAR OF STONE AROUND AN ALUMINUM POST WITH CAP MARKED;




NE 1/16 CORNER OF SECTION 8

SET AN ALUMINUM POST, 30 INCHES LONG, ON BEDROCK, BUILT A 2 FOOT COLLAR OF STONE AROUND AN ALUMINUM POST WITH CAP MARKED;



C-N 1/16 CORNER OF SECTION 8

SET AN ALUMINUM POST, 30 INCHES LONG, 24 INCHES IN GROUND WITH CAP MARKED,



### RUIDOSO LAND SURVEYING COMPANY

SURVEYING-MAPPING-PLANNING  
P.O. BOX 537, RUIDOSO, N.M. 88345  
2907 1/2 SUDDERTH, PH. 257-2818

DATE	SCALE
8/18/94	1"=600'
PLAT NUMBER	JOB NUMBER
A-92	1929
SHEET NUMBER	PLATTED BY
1 OF 1	RAS



Wyatt A. Sparks  
R.P.L.S. N.M. 8487

SURVEY PLAT  
SEC. 5,6,7,8, T18S R15E  
BK 46 Pg 13-14